

# University of California Curation Center

## Merritt Object Modeling

Rev. 0.5 – 2010-06-03

### 1 Introduction

Information technology and resources have become integral and indispensable to the pedagogic mission of the University of California. Members of the UC community routinely produce and utilize a wide variety of digital assets in the course of teaching, learning, and research. These assets represent the intellectual capital of the University; they have inherent enduring value and need to be managed carefully to ensure that they will remain available for use by future scholars. Within the UC system the UC Curation Center (UC3) of the California Digital Library (CDL) has a broad mandate to ensure the long-term usability of the digital assets of the University. UC3 views its mission in terms of *digital curation*, the set of policies and practices aimed at maintaining and adding value to authentic digital assets for use by scholars now and into the indefinite future [Abbott].

In order to meet these obligations UC3 is developing Merritt, an emergent approach to digital curation infrastructure [Merritt]. Merritt devolves infrastructure function into a growing set of granular, orthogonal, but interoperable micro-services embodying curation values and strategies [Foundations]. Since each of the services is small and self-contained, they are collectively easier to develop, deploy, maintain and enhance [Denning]; equally as important, since the level of investment in and commitment to any given service is small, they are more easily replaced when they have outlived their usefulness. Yet at the same time, complex curation functionality can emerge from the strategic combination of individual, atomistic services [Fisher].

NOTE The key words “MUST”, “MUST NOT”, “REQUIRED”, “SHALL”, “SHALL NOT”, “SHOULD”, “SHOULD NOT”, “RECOMMENDED”, “MAY”, and “OPTIONAL” are to be interpreted as described in RFC 2119 [RFC2119].

### 2 Object modeling

Digital content curated in a Merritt environment typically will be managed by the Merritt Storage service. The Storage service imposes minimal structural requirements on the digital content that is managed in it; in particular, Storage-managed content is not typed so the service has no understanding of object semantics. Additional requirements are necessary to facilitate the management of object semantics. These requirements will be enforced by the Ingest service and the resulting object semantics will be exposed via the Inventory service.

Merritt defines an *object* as the representation in digital form of a coherent intellectual *work*, c.f. [FRBR]. An object is composed of an arbitrary number of *versions*, each representing a discrete state of the object and further composed of an arbitrary number of files, c.f. [Dflat].

In order to represent the significant properties of the components of an object, a Merritt object **MUST**

contain a special component that is an ORE *resource map* [ORE]. A resource map provides a flexible and extensible mechanism for describing aggregations of resources in terms of RDF triples [RDF].

NOTE An RDF triple is an assertion with the generalized form “*subject predicate object*”, where the predicate defines the relation existing between subject and object.

Merritt resource maps **MUST** be serialized in Turtle [Turtle].

NOTE The ORE specification currently only defines serializations in RDF/XML, RDFa, and Atom/XML. Thus, Turtle is a non-standard ORE serialization. However, Turtle has the significant benefit of far greater transparency for the human reader.

The minimal Merritt object resource map is:

```
# Minimal Merritt object version resource map
@prefix mrt: <http://merritt.cdlib.org/terms#>.
@prefix ore: <http://www.openarchives.org/ore/terms/>.
<object-url>
  ore:aggregates                # Object files
    <file-url>,
    ...,
    <file-url>,
    <resource-map-url>;
mrt:objectType                  # Object type
  "type";
mrt:objectRole                  # Object role
  "role";
mrt:primaryIdentifier           # Object primary identifier
  "primary-identifier".
<resource-map-url>
  ore:describes                  # Resource map declaration
    <object-url>;
mrt:mimeType                    # Resource map serialization
  "text/turtle".
```

NOTE Resource map examples use the Turtle “,” and “;” abbreviation symbols. It is possible, and acceptable, to express functionally equivalent resource maps using more verbose alternative expressions.

The Resource map **MUST** define all object components and declare the object’s type, role, and primary identifier. Note that the resource map **MUST** also include a reference to itself as a member of the object aggregation.

An object’s type indicates its nature within a Merritt curation environment:

Identifier	Object type
MRT-curatorial	A Merritt curatorial object. Curatorial objects are those representing content originating from external curatorial contributors.
MRT-system	A Merritt system object. System objects are those necessary for the internal operation of the Merritt curatorial environment.

Table 1 – Merritt object types

An object’s role further indicates its function within a Merritt curation environment:

Identifier	Object type	Object role
MRT-collection	MRT-curatorial	A Merritt curatorial collection object. Collection objects represent arbitrary administrative groups of objects.
MRT-content		A Merritt curatorial content object. Content objects represent individual abstract works.
	MRT-system	Reserved for future use.

Table 2 – Merritt object roles

Additional object types and roles MAY be defined as necessary.

Some of an object’s file components may be considered to represent the primary information content of the object, i.e. they are *data*; while other files may be descriptive of object components, i.e. they are *metadata*. Metadata may apply at any component level: the entire object, a particular version, a subset of version files, or a single file. The expression of metadata must conform to the semantics of a specific schema, as indicated by the “mrt:metadataSchema” property, and the syntax of the specific encoding and serialization, as indicated by the “mrt:mimeType” property.

All metadata relationships SHOULD be specified with appropriate resource map assertions. For example, it is RECOMMENDED that a Merritt object defines a local identifier, resolvable to an appropriate descriptive record in an external discovery system; asserts its membership in appropriate administrative classes; and includes a minimal Electronic Record Citation (ERC) description [ERC]:

```
# Object local identifier, class memberships, and ERC description
@prefix mrt: <http://merritt.cdlib.org/terms#>.
<object-url>
  mrt:localIdentifier          # Object local identifier
    "local-identifier";
  mrt:hasMetadata             # Object metadata
    <membership-file-url>,    # Object membership component
    <erc-file-url>.           # Object ERC component
<membership-file-url>
  mrt:metadataSchema          # Membership schema declaration
    "MRT-membership";
  mrt:mimeType                 # Membership serialization
    "text/anvl";
```

```
<erc-file-url>
  mrt:metadataSchema           # ERC schema declaration
    "ERC";
  mrt:mimeType                 # ERC serialization
    "text/anvl".
```

NOTE Until such time as a formal MIME type for the ANVL [ANVL] is established at the IANA registry, the experimental MIME type “text/x-anvl” SHOULD be used.

The object local identifier SHOULD be meaningful in the local context of the object’s curator. In general, this identifier SHOULD resolve to a more detailed descriptive catalog record for the object external to the Merritt curation environment.

An object can assert membership in an arbitrary number of administrative classes. The class membership mechanism MAY be used to define curatorial collections and other significant administrative object categories. The object membership component MUST list all of the classes of which the object is a member.

```
class
  ...
```

NOTE An ellipsis (“...”) indicates arbitrary repetition of the previous element.

The object ERC component MUST define the four REQUIRED Dublin Kernel elements represented in ANVL form:

```
erc:
  who: creator
  what: title
  when: date
  where: primary-identifier
  [ where: local-identifier ]
  [ how: methodology ]
  [ why: exposition ]
```

NOTE Brackets [ and ] enclose optional elements.

The “who” element SHOULD identify a person or party responsible in some manner for the object; the “what” element SHOULD define a human-readable title for the object; the “when” element SHOULD describe the object’s creation date; and the “where” element SHOULD specify the object’s primary identifier. An additional OPTIONAL “where” element MAY specify the object’s local identifier, which SHOULD resolve to a more complete descriptive metadata record external to the Merritt curation environment. The OPTIONAL “how” element SHOULD express the methodology of the object’s creation; and the “why” element SHOULD provide an expository note regarding the object’s creation.

NOTE Object descriptive metadata should be meaningful in the object’s curatorial context. In general, this description should be at the level of a FRBR work, rather than expression or manifestation [FRBR].

This description is intended to provide a useful, but relatively simple overview of the object; in particular, it is *not* intended as a substitute for complete cataloging, which is expected to exist external to the Merritt curation environment at the location provided by the local identifier.

Required Kernel element values that cannot be supplied MUST use one of the pre-defined coded values appropriate to the nature of the omission, for example, “(:unas)” (unassigned), “(:unkn)” (unknown), or “(:null)” (meaningfully empty), c.f. [ERC].

Additional metadata MAY be associated with the object. Metadata semantics MUST be declared using one of the following literal schema identifiers as the object of a “mrt:hasMetadata” property. Object producers with latitude regarding metadata file names SHOULD use the reserved file names associated with the various schemas.

<b>Identifier</b>	<b>File name (recommended)</b>	<b>Metadata schema</b>
AES-X098B	mrt-aes-x098b.xml	AES-X098B audio technical metadata.
CreativeCommons	mrt-creative-commons.xml	Creative Commons rights metadata.
DublinCore	mrt-dublin-core.xml	Dublin Core metadata.
ERC	mrt-erc.txt	Electronic Resource Citation descriptive metadata.
JHOVE2	mrt-jhove2.xml	JHOVE2 characterization metadata,
MARCXML	mrt-marcxml.xml	MARC bibliographic metadata.
MIX	mrt-mix.xml	MIX / NISO Z39.87 still image technical metadata.
MODS	mrt-mods.xml	MODS descriptive metadata.
MRT-ingest	mrt-ingest.txt	Merritt ingest metadata.
MRT-membership	mrt-membership.txt	Merritt class membership assertions.
PREMIS-object	mrt-premis-object.xml	PREMIS object preservation metadata.
PREMIS-rights	mrt-premis-rights.xml	PREMIS rights preservation metadata.
VRA-core	mrt-vra-code.xml	VRA Core cultural heritage metadata.

Table 3 – Metadata schemas

NOTE Within a Merritt curation environment all file system names beginning with “merritt” or “mrt” (on a case-insensitive basis) are reserved.

Additional metadata schemas MAY be defined as necessary.

### 3 Ontological classes and relationships

Merritt makes use of ontological classes and properties defined in the following namespaces.

<b>Prefix</b>	<b>URI</b>	<b>Ontology</b>
cc	http://creativecommons.org/ns#	Creative Commons rights metadata.
dc	http://purl.org/dc/elements/1.1/	Dublin Core metadata elements.
dcterms	http://purl.org/dc/terms/	Dublin Core metadata terms.
ore	http://www.openarchives.org/ore/terms	ORE aggregation terms.
mrt	http://merritt.cdlib.org/terms#	Merritt classes and properties.
rdf	http://www.w3.org/1999/02/22-rdf-syntax-ns#	RDF vocabulary terms.
rdfs	http://www.w3.org/2001/01/rdf-schema#	RDF Schema vocabulary terms.

Table 4 – Merritt namespaces

Additional namespaces MAY be defined as necessary.

Merritt defines a number of its own ontological classes and properties, all in the “mrt” namespace.

### 3.1 Merritt classes

The following Merritt classes are defined.

<b>mrt:Component</b>	
rdf:label	Component
rdf:comment	Abstract Merritt class for object model components: object, version, file.
rdf:type	rdf:Class

<b>mrt:File</b>	
rdf:label	File
rdf:comment	Merritt class for files. A file is a formatted octet stream.
rdf:type	rdf:Class
rdf:subClassOf	mrt:Component

<b>mrt:Object</b>	
rdf:label	Object
rdf:comment	Merritt class for objects. An object is the representation in digital form of an abstract work. An object is composed of an arbitrary number of versions.
rdf:type	rdf:Class
rdf:subClassOf	mrt:Component
rdfs:seeAlso	mrt:Version



<b><i>mrt:Version</i></b>	
rdf:label	Version
rdf:comment	Merritt class for versions. A version is a set of files that collectively represents a discrete state of an object. A version is composed of an arbitrary number of files.
rdf:type	rdf:Class
rdf:subClassOf	mrt:Component
rdfs:seeAlso	mrt:Object
rdfs:seeAlso	mrt:File

### 3.2 Merritt properties

The following Merritt properties are defined.

<b><i>mrt:hasPreview</i></b>	
rdf:label	hasPreview
rdf:comment	Merritt property asserting that an object has a preview representation. The preview representation should present a concise summary of the object, such as a thumbnail for an image or an abstract for a document.
rdf:type	rdf:Property
rdfs:domain	mrt:Object
rdfs:range	mrt:File

<b><i>mrt:hasMetadata</i></b>	
rdf:label	hasMetadata
rdf:comment	Merritt property asserting that an object component has metadata. Metadata provide further information about the component.
rdf:type	rdf:Property
rdfs:domain	mrt:Component
rdfs:range	mrt:File

<b><i>mrt:isDerivativeOf</i></b>	
rdf:label	isDerivativeOf
rdf:comment	Merritt property asserting that an object component is a derivative of another component. Note that both components must be of the same type. For example, a file can only be a derivative of another file.
rdf:type	rdf:Property
rdfs:domain	mrt:Component
rdfs:range	mrt:Component



<b><i>mrt:localIdentifier</i></b>	
rdf:label	localIdentifier
rdf:comment	Merritt property asserting that an object has a local identifier. A local identifier should be meaningful in the object's curatorial context and may resolve to a descriptive metadata record for the object in a discovery service external to a Merritt curation environment.
rdf:type	rdf:Property
rdfs:domain	mrt:Object
rdfs:range	rdf:Literal

<b><i>mrt:metadataSchema</i></b>	
rdf:label	metadataSchema
rdf:comment	Merritt property asserting that a file contains metadata conforming to a particular schema.
rdf:type	rdf:Property
rdfs:domain	mrt:File
rdfs:range	rdf:Literal

<b><i>mrt:mimeType</i></b>	
rdf:label	mimeType
rdf:comment	Merritt property asserting that a file has a particular MIME type. MIME types must either be registered in the IANA registry or be experimental types.
rdf:type	rdf:Property
rdfs:domain	mrt:File
rdfs:range	rdf:Literal

<b><i>mrt:objectRole</i></b>	
rdf:label	objectRole
rdf:comment	Merritt property asserting that an object has a particular role.
rdf:type	rdf:Property
rdfs:domain	mrt:Object
rdfs:range	rdf:Literal

<b><i>mrt:objectType</i></b>	
rdf:label	objectType
rdf:comment	Merritt property asserting that an object is of a particular type.
rdf:type	rdf:Property
rdfs:domain	mrt:Object
rdfs:range	rdf:Literal



<i>mrt:primaryidentifier</i>	
rdf:label	primaryIdentifier
rdf:comment	Merritt property asserting that an object has a primary identifier. A primary identifier is the unique and persistent identifier used by a Merritt curation environment to identify the object.
rdf:type	rdf:Property
rdfs:domain	mrt:Object
rdfs:range	rdf:Literal

## 4 File system expression

Object components may originate from the object's producer, an object consumer, or be generated automatically by a Merritt service. The primary obligation of a Merritt curation environment is to ensure the long-term viability of producer-supplied content. There is a somewhat lower obligation regarding system-generated content, which presumably can be regenerated as necessary; and consumer-supplied content, which by definition originates outside of the object's primary curatorial context. The distinction between component provenance is explicitly represented in the file system representation of an object, c.f. [Dflat].

```

consumer/
  [ consumer-supplied-files
    ... ]
producer/
  [ producer-supplied-files
    ... ]
system/
  [ mrt-erc.txt ]
  [ mrt-ingest.txt ]
  [ mrt-membership.txt ]
  mrt-object-map.ttl
  [ system-generated-files
    ... ]

```

By convention the file “mrt-object-map.ttl” is the Merritt object resource map automatically generated by the Merritt Ingest service at the time of submission.

The full form of an object resource map is:

```

# Merritt object version resource map
@prefix mrt: <http://merritt.cdlib.org/terms#>.
@prefix ore: <http://www.openarchives.org/ore/terms/>.
<object-url>
  ore:aggregates                # Object files
    <file-url>,
    ...,
    <file-url>,
    <resource-map-url>;

```



```

mrt:objectType                # Object type
  "type";
mrt:objectRole                # Object role
  "role";
mrt:primaryIdentifier         # Object primary identifier
  "primary-identifier" [ ;
mrt:localIdentifier          # Object local identifier
  "local-identifier" ] [ ;
mrt:hasMetadata              # Object metadata
[ <ingest-file-url> ] [ ,
  <membership-file-url> ] [ ,
  <erc-file-url> ] [ ,
  <metadata-file-url> ] [ ,
  ... ] [ ;
mrt:hasPreview               # Object preview component
  <preview-file-url> ] .
<resource-map-url>
  ore:describes              # Resource map declaration
  <object-url>;
  mrt:mimeType                # Resource map serialization
  "text/turtle".
[ <membership-file-url>
  mrt:metadataSchema        # Membership schema declaration
  "MRT-membership";
  mrt:mimeType                # Membership serialization
  "text/anvl". ]
[ <erc-file-url>
  mrt:metadataSchema        # ERC schema declaration
  "ERC";
  mrt:mimeType                # ERC serialization
  "text/anvl". ]
[ <metadata-file-url>
  mrt:metadataSchema        # Metadata schema declaration
  "schema";
  mrt:mimeType                # Metadata serialization
  "mime". ]
...

```

## References

- [Abbott] Daisy Abbott, *What is Digital Curation?* April 3, 2008  
 <<http://www.dcc.ac.uk/resource/briefing-papers/what-is-digital-curation/>>.
- [Denning] Peter J. Denning, Chris Gunderson, and Rich Hayes-Roth, "Evolutionary system development," *Communications of the ACM* 51:17 (December 2008): 29-31.
- [Dflat] UC3, *Dflat: A Simple File System Convention for Digital object Storage*, 2010.
- [ERC] J. Kunze and A. Turner, *Kernel Metadata and Electronic Resource Citations*, April 28, 2009

<<http://dublincore.org/kernelwiki/FrontPage?action=AttachFile&do=get&target=ercspec.html>>.

- [Fisher] David A. Fisher, *An Emergent Perspective on Interoperation in Systems of Systems*, CMU/SEI-2006-TR-003, ESC-TR-2006-003, March 2006  
<<http://www.sei.cmu.edu/pub/documents/06.reports/pdf/06tr003.pdf>>.
- [Foundations] UC3, *Digital Preservation Program: Foundations*, 2010.
- [FRBR] IFLA Study Group on the Functional Requirements for Bibliographic Records, *Functional Requirements for Bibliographic Records – Final Report*, UBCIM 19 (February 2009; München: K. G. Saur, 1998).
- [Merritt] UC3, *Merritt: An Emergent Approach to Digital Curation Infrastructure*, 2010.
- [MIME] IANA, *MIME Media Types*, 2010 <<http://www.iana.org/assignments/media-types>>.
- [ORE] Carl Lagoze, Herbert Van de Sompel, Pete Johnston, Michael Nelson, Robert Sanderson, and Simeon Warner, eds., *ORE User Guide – Primer*, October 17, 2008  
<<http://www.openarchives.org/ore/primer>>.
- [RDF] Graham Klyne and Jeremy J. Carroll, eds., *Resource Description Framework (RDF): Concepts and Abstract Syntax*, W3C Recommendation, February 10, 2004 <<http://www.w3.org/TR/rdf-concepts/>>.
- [RFC2119] S. Bradner, *Key Words for Use in RFCs to Indicate Requirement Levels*, BCP 14, RFC 2119, March 1997 <<http://www.ietf.org/rfc/rfc2119.txt>>.
- [Turtle] David Beckett and Tim Berners-Lee, *Turtle – Terse RDF Triple Language*, January 14, 2008  
<<http://www.w3.org/TeamSubmission/turtle/>>.